

Ball Valves, BV15FL, BV15YFL, BV15C & BV20FL, BV20YFL, BV20C

BV15FL & BV20FL FEATURES

- DR Brass
- 15mm and 20mm FL x FL
- Full bore
- Maximum operating temp. to 90°C
- AGA 6515
- Maximum pressure 2500kPa



BV15FL
15MM FL X FL



BV20FL
20MM FL X FL



BV15YFL & BV20YFL FEATURES

- 15mm and 20mm FL x FL
- Full bore
- Maximum operating temp. to 90°C
- AGA 6515
- Maximum pressure 2500kPa

BV15YFL
15MM FL X FL



BV20YFL
20MM FL X FL



BV15C & BV20C FEATURES

- DR Brass
- Compression nut and copper olive
- 15mm and 20mm C x C
- Full bore
- Maximum operating temp. to 90°C
- Watermark ATS 5200.012
Lic No 020042
- Maximum pressure 2500kPa



BV15C
15MM C X C



BV20C
20MM C X C



DISCLAIMER: Every care has been taken in the preparation of these instructions, which have been issued as a guide only. Compliance with the requirements of local Authorities is required at all times. These requirements may change from time to time. Always be aware of the local requirements. Subject to any statutory obligations and manufacturers warranties no liability can be accepted for any losses, consequential or otherwise which may arise or be said to have arisen from relying upon the contents of this installation instruction as to the fitness of any particular product for any particular purpose, use or application. The Australian Valve Group Pty Ltd reserves the right to modify designs and specifications and to withdraw and introduce products at any time without notice.